

View Online at <https://aerobasegroup.com/nsn/3950-01-255-8857>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Maximum Lift Height:

45.0 feet

Flange Width:

7.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

Any acceptable

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Motor driven

Maximum Traversing Speed:

70.0 feet per minute

Track Height:

6.375 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

32.000 inches

Wheel Center To Center Distance:

15.250 inches

Maximum Load Rating:

4000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Air to air cooled

Voltage In Volts:

460.0

Phase:

Three

Frequency In Hertz:

60.0

Specification Or Standard:

1 type and h-4 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800