

View Online at <https://aerobasegroup.com/nsn/3950-01-268-5992>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Any acceptable

Maximum Lift Height:

32.0 feet

Flange Width:

7.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Travel Rate Per Minute:

22.0 feet

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

1.50 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Hand geared

Maximum Traversing Speed:

70.000 feet per minute

Track Height:

Any acceptable

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

17.000 inches

Wheel Center To Center Distance:

29.625 inches

Maximum Load Rating:

2000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Air to air cooled

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800