

View Online at <https://aerobasegroup.com/nsn/3950-01-281-4337>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Travel Rate Per Minute:**

15.0 feet and 5.00 feet

**Mechanical Advantage Method:**

Spur gear

**Braking Method:**

Electric and manual

**Hook Quantity:**

1

**Power Requirement Rating:**

2.00 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

20.125 inches

**Maximum Load Rating:**

4000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Air to air cooled

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

Electric push botton control w/7.00 ft drop; 1.531 in. Hook throat opening

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800