

View Online at <https://aerobasegroup.com/nsn/3950-01-283-1767>

**Prime Mover Quantity:**

1

**Power Drive Operating Pressure:**

90.0 pounds per square inch gage

**Maximum Lift Height:**

10.0 feet

**Flange Width:**

Between 3.000 inches and 4.000 inches

**Chain Type:**

Die lock link

**Prime Mover Type:**

Pneumatic motor

**Operation Method:**

Power

**Mechanical Advantage Method:**

Multiple gear

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Suspension Mounting Method:**

Trolley

**Trolley Suspension Style:**

Plain, standard i beam, wheels vertical

**Trolley Type:**

Motor driven

**Maximum Traversing Speed:**

69.0 feet per minute

**Track Height:**

Any acceptable

**Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:**

6.500 inches

**Wheel Center To Center Distance:**

7.000 inches

**Chain Material Diameter:**

Any acceptable

**Maximum Load Rating:**

2200.0 pounds

**Mounting Position:**

Any acceptable

**Cooling Method:**

Any acceptable

**Special Features:**

With hand crank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800