NSN 3950-01-288-7134

Chain Hoist - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3950-01-288-7134

Pneumatic motor Operation Method: Power Load Limit At Selected Speed And Drum Location: 2200.0 pounds single speed first drum Travel Rate Per Minute: 10.0 feet and 25.0 feet Hook Quantity: 1 Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Prime Mover Type:
Power Load Limit At Selected Speed And Drum Location: 2200.0 pounds single speed first drum Travel Rate Per Minute: 10.0 feet and 25.0 feet Hook Quantity: 1 Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Pneumatic motor
Load Limit At Selected Speed And Drum Location: 2200.0 pounds single speed first drum Travel Rate Per Minute: 10.0 feet and 25.0 feet Hook Quantity: 1 Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Operation Method:
2200.0 pounds single speed first drum Travel Rate Per Minute: 10.0 feet and 25.0 feet Hook Quantity: 1 Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Power
Travel Rate Per Minute: 10.0 feet and 25.0 feet Hook Quantity: 1 Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Load Limit At Selected Speed And Drum Location:
10.0 feet and 25.0 feet Hook Quantity: 1 Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	2200.0 pounds single speed first drum
Hook Quantity: 1 Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Travel Rate Per Minute:
Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	10.0 feet and 25.0 feet
Suspension Mounting Method: Trolley Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Hook Quantity:
Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	1
Trolley Suspension Style: Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Suspension Mounting Method:
Plain, standard i beam, wheels vertical Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Trolley
Trolley Type: Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Trolley Suspension Style:
Motor driven Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Plain, standard i beam, wheels vertical
Track Height: 4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Trolley Type:
4.000 inches Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Motor driven
Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position: 18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	Track Height:
18.000 inches Shelf Life: N/a Unit Of Measure: Demilitarization: No	4.000 inches
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:
N/a Unit Of Measure: Demilitarization: No	18.000 inches
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization: No	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A02800	A02800