

View Online at <https://aerobasegroup.com/nsn/3950-01-298-5223>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 remote control and 1 safety snap hook and 1 wire rope

Environmental Protection:

Any acceptable

Maximum Lift Height:

50.0 feet

Flange Width:

Between 3.625 inches and 6.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Load Limit At Selected Speed And Drum Location:

2000.0 pounds single speed first drum

Travel Rate Per Minute:

32.0 feet

Mechanical Advantage Method:

Multiple gear

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

2.00 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Geared, standard i beam, wheels, vertical

Trolley Type:

Motor driven

Maximum Traversing Speed:

100.0 feet per minute

Track Height:

6.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

22.312 inches

Wheel Center To Center Distance:

10.125 inches

Mounting Position:

Any acceptable

Cooling Method:

Air to air cooled

Voltage In Volts:

208.0 and 230.0 and 460.0 and 575.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800