

View Online at <https://aerobasegroup.com/nsn/3950-01-298-5223>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 remote control and 1 safety snap hook and 1 wire rope

**Environmental Protection:**

Any acceptable

**Maximum Lift Height:**

50.0 feet

**Flange Width:**

Between 3.625 inches and 6.000 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Load Limit At Selected Speed And Drum Location:**

2000.0 pounds single speed first drum

**Travel Rate Per Minute:**

32.0 feet

**Mechanical Advantage Method:**

Multiple gear

**Braking Method:**

Electric

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

2.00 horsepower

**Suspension Mounting Method:**

Trolley

**Trolley Suspension Style:**

Geared, standard i beam, wheels, vertical

**Trolley Type:**

Motor driven

**Maximum Traversing Speed:**

100.0 feet per minute

**Track Height:**

6.000 inches

**Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:**

22.312 inches

**Wheel Center To Center Distance:**

10.125 inches

**Mounting Position:**

Any acceptable

**Cooling Method:**

Air to air cooled

**Voltage In Volts:**

208.0 and 230.0 and 460.0 and 575.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800