

View Online at <https://aerobasegroup.com/nsn/3950-01-308-3467>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Corrosion resistant and fungus resistant

Chain Type:

Proof coil

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Intermittent

Operation Method:

Power

Mechanical Advantage Method:

Multiple gear

Braking Method:

Electric and manual

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

3.00 horsepower

Suspension Mounting Method:

Hook

Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:

23.000 inches

Chain Material Diameter:

0.438 inches

Maximum Load Rating:

4000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Air to air cooled

Voltage In Volts:

208.0

Phase:

Three

Special Features:

Corrosion/fungus resistant and splash proof are optional and not included; 2 speed 8/24 fpm; 53 ft lift; 49 ft control cable; chain bucket and weather protection

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800