

View Online at <https://aerobasegroup.com/nsn/3950-01-308-3467>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Power

**Mechanical Advantage Method:**

Multiple gear

**Braking Method:**

Electric and manual

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

3.00 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

23.000 inches

**Chain Material Diameter:**

0.438 inches

**Maximum Load Rating:**

4000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Air to air cooled

**Voltage In Volts:**

208.0

**Phase:**

Three

**Special Features:**

Corrosion/fungus resistant and splash proof are optional and not included; 2 speed 8/24 fpm; 53 ft lift; 49 ft control cable; chain bucket and weather protection

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800