

View Online at <https://aerobasegroup.com/nsn/3950-01-337-3834>

**Prime Mover Quantity:**

1

**Power Drive Operating Pressure:**

2000.0 pounds per square inch gage

**Chain Type:**

Proof coil or stud link

**Prime Mover Type:**

Hydraulic motor

**Operation Method:**

Power

**Capstan Spool Mounting Position:**

Vertical

**Capstan Spool Style:**

Single head

**Capstan Spool Surface Design:**

Plain

**Capstan Spool Quantity:**

2

**Whelped Wheel Quantity:**

1

**Err Default:**

Err default

**Load Limit At Selected Speed And Drum Location:**

10000.0 pounds single speed first drum and 3500.0 pounds single speed second drum

**Travel Rate Per Minute:**

30.0 feet and 36.0 feet

**Mechanical Advantage Method:**

Multiple gear

**Braking Method:**

Manual

**Err Default:**

Err default

**Largest Diameter And Location:**

18.000 inches first spool

**Overall Length And Location:**

16.000 inches first spool

**Chain Material Diameter:**

1.313 inches

**Maximum Load Rating:**

10000.0 pounds

**Cooling Method:**

Air to air cooled

**Special Features:**

Capstan windlass system provided for the t-agos class ships

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800