

View Online at <https://aerobasegroup.com/nsn/3950-01-346-7821>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller

Environmental Protection:

Any acceptable

Maximum Lift Height:

20.0 feet

Flange Width:

2.500 inches

Chain Type:

Proof coil

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Power

Travel Rate Per Minute:

16.0 feet

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

0.500 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Motor driven

Maximum Traversing Speed:

35.0 feet per minute

Track Height:

Between 6.000 inches and 18.000 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

17.250 inches

Wheel Center To Center Distance:

5.250 inches

Err Default:

Err default

Maximum Load Rating:

1000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Air to air cooled

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

5.0ft.Min radius

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800