

View Online at <https://aerobasegroup.com/nsn/3950-01-346-7821>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller

**Environmental Protection:**

Any acceptable

**Maximum Lift Height:**

20.0 feet

**Flange Width:**

2.500 inches

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Operation Method:**

Power

**Travel Rate Per Minute:**

16.0 feet

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

0.500 horsepower

**Suspension Mounting Method:**

Trolley

**Trolley Suspension Style:**

Plain, standard i beam, wheels vertical

**Trolley Type:**

Motor driven

**Maximum Traversing Speed:**

35.0 feet per minute

**Track Height:**

Between 6.000 inches and 18.000 inches

**Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:**

17.250 inches

**Wheel Center To Center Distance:**

5.250 inches

**Err Default:**

Err default

**Maximum Load Rating:**

1000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Air to air cooled

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

5.0ft.Min radius

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800