

View Online at <https://aerobasegroup.com/nsn/3950-01-352-2248>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 safety snap hook

Environmental Protection:

Any acceptable

Maximum Lift Height:

16.0 feet

Chain Type:

Proof coil

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Power

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

0.50 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, standard i beam, wheels vertical

Trolley Type:

Motor driven

Maximum Traversing Speed:

100.0 feet per minute

Track Height:

5.125 inches

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

17.250 inches

Wheel Center To Center Distance:

5.250 inches

Maximum Load Rating:

1000.0 pounds

Mounting Position:

Parallel

Cooling Method:

Any acceptable

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800