

View Online at <https://aerobasegroup.com/nsn/3950-01-370-6352>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Hand and power

**Drum Flange To Flange Distance And Location:**

5.000 inches first drum

**Drum Diameter And Location:**

4.000 inches first drum

**Drum Flange Diameter And Location:**

7.000 inches first drum

**Load Limit At Selected Speed And Drum Location:**

1000.0 pounds single speed first drum

**Travel Rate Per Minute:**

30.0 feet

**Braking Method:**

Electric

**Power Requirement Rating:**

1.500 horsepower

**Drum Surface Design:**

Plain

**Cooling Method:**

Air to air cooled

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Manual brake release for emergency; hand crank for emergency operation; drum reversing switch nema 4 rated; 15 minute duty cycle on motor; belt driven

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800