

View Online at <https://aerobasegroup.com/nsn/3950-01-441-5683>

Prime Mover Quantity:

1

Current Type:

Ac

Environmental Protection:

Submersible and fungus resistant and spray tight

End Application:

Wasp class lhd

Maximum Lift Height:

30.0 feet

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Powered

Load Limit At Selected Speed And Drum Location:

12000.0 pounds single speed first drum

Travel Rate Per Minute:

0.75 feet and 4.00 feet and 13.00 feet

Braking Method:

Electric

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

0.50 horsepower

Suspension Mounting Method:

Trolley

Trolley Suspension Style:

Plain, wide flange i beam, flat flange

Trolley Type:

Motor driven

Track Underside Distance To Load Hook Bearing Surface In Fully Raised Position:

31.250 inches

Wheel Center To Center Distance:

32.000 inches

Mounting Position:

Right angle

Cooling Method:

Air to air cooled

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Navy wsdc jkn, wasp class lhd

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800