

View Online at <https://aerobasegroup.com/nsn/3950-01-452-1209>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Furnished Items And Quantity:**

1 motor controller and 1 remote control and 1 safety snap hook

**Environmental Protection:**

Any acceptable

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Operation Method:**

Powered

**Load Limit At Selected Speed And Drum Location:**

1000.0 kilograms single speed first drum

**Travel Rate Per Minute:**

32.0 feet

**Mechanical Advantage Method:**

Multiple gear

**Braking Method:**

Electric and mechanical

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

2.50 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

Between 19.100 inches and 21.500 inches

**Maximum Load Rating:**

1000.0 kilograms

**Mounting Position:**

Parallel

**Cooling Method:**

Self-ventilated

**Voltage In Volts:**

460.0

**Phase:**

Three

**Special Features:**

Hook or eyebolt mounted; nonventilated, weatherproof enclosure; includes 50 ft power cord

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800