

View Online at <https://aerobasegroup.com/nsn/3950-01-452-1213>

Prime Mover Quantity:

1

Current Type:

Ac

Furnished Items And Quantity:

1 motor controller and 1 remote control and 1 safety snap hook

Environmental Protection:

Any acceptable

Chain Type:

Proof coil

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Duty Cycle:

Continuous

Operation Method:

Powered

Load Limit At Selected Speed And Drum Location:

1000.0 kilograms single speed first drum

Travel Rate Per Minute:

32.0 feet

Mechanical Advantage Method:

Multiple gear

Braking Method:

Electric and mechanical

Hook Quantity:

1

Load Element Quantity Per Hook:

1

Power Requirement Rating:

2.50 horsepower

Suspension Mounting Method:

Hook

Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:

Between 19.100 inches and 21.500 inches

Maximum Load Rating:

1000.0 kilograms

Mounting Position:

Parallel

Cooling Method:

Self-ventilated

Voltage In Volts:

460.0

Phase:

Three

Special Features:

Hook or eyebolt mounted; non-ventilated, weatherproof enclosure; includes 20 ft power cord

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800