

View Online at <https://aerobasegroup.com/nsn/3950-01-485-1713>

**End Application:**

Stationary mounted hoist

**Maximum Lift Height:**

66.0 feet

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Operation Method:**

Powered

**Travel Rate Per Minute:**

21.0 feet

**Braking Method:**

Electric and manual

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

3.00 horsepower

**Suspension Mounting Method:**

Lug

**Trolley Type:**

Motor driven

**Maximum Traversing Speed:**

35.0 feet per minute

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

1.688 inches

**Maximum Load Rating:**

4000.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Air to air cooled

**Product Name:**

2 ton wire rope hoist 3 phase with 4 button controls

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

Single reeved 2 part 0.312inch diameter wire rope

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800