

View Online at <https://aerobasegroup.com/nsn/3950-01-502-3452>

**Prime Mover Quantity:**

1

**Current Type:**

Ac

**Environmental Protection:**

Any acceptable

**Chain Type:**

Proof coil

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Continuous

**Operation Method:**

Powered

**Travel Rate Per Minute:**

32.0 feet

**Braking Method:**

Electric

**Hook Quantity:**

1

**Load Element Quantity Per Hook:**

1

**Power Requirement Rating:**

0.50 horsepower

**Suspension Mounting Method:**

Hook

**Raised Position Distance Between Suspension Hook And Load Hook Bearing Surface:**

15.750 inches

**Maximum Load Rating:**

500.0 pounds

**Mounting Position:**

Parallel

**Cooling Method:**

Any acceptable

**Product Name:**

Hook mount link chain electric hoist

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

0.250 ton capacity; 32 fpm speed; 36 ft lift length; hook mount link chain; 230/460 v, 3 phase

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800