Power Operated Drum Winch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3950-01-518-6663

Prime Mover Quantity:

1

Current Type:

Dc

Furnished Items And Quantity:

1 remote control

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Operation Method:

Electrical

Drum Flange To Flange Distance And Location:

9.950 inches first drum

Drum Diameter And Location:

4.000 inches first drum

Drum Flange Diameter And Location:

8.240 inches first drum

Load Limit At Selected Speed And Drum Location:

0.0 pounds single speed first drum and 3000.0 pounds second speed first drum and 6000.0 pounds third speed first drum and 9000.0

pounds fourth speed first drum

Travel Rate Per Minute:

51.0 feet and 16.0 feet and 10.0 feet and 5.0 feet

Braking Method:

Manual and mechanical

Power Requirement Rating:

2.5 watts

Product Name:

Warn series 9 dc winch

Voltage In Volts:

24.0

Special Features:

rated load 9, 000 lbs; wire rope recommended 1/2 inch 26, 600 lbs breaking strength; cotactor industrial contactor with 32 ft heavy duty remote control; approx shipping weight 95 lbs; available accessories over load interrup, tensioner kit, remote clutch kit and roller fairlead; standard compliance sae j706, nfpa 1901-73 and ce machinery directive 98/37/eec

Functional Description:

Yfeatures a weatherproof industrial contactor and heavy duty remote control; disc brake is designed for extended power-out use and the motor is protected by a thermal overload switch; high gear ratio of 199: 1 provides fast line speed

Type/model Designation:

Series 9 dc

Shelf Life:

N/a

Unit Of Measure:

Domilitorization

NSN 3950-01-518-6663

Power Operated Drum Winch - Page 2 of 2

Fiig: A02800

