

View Online at <https://aerobasegroup.com/nsn/3950-01-521-0086>

**Prime Mover Quantity:**

1

**Prime Mover Type:**

Hydraulic motor

**Operation Method:**

Powered

**Drum Flange To Flange Distance And Location:**

13.750 inches first drum err-100

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Style:**

Single head

**Load Limit At Selected Speed And Drum Location:**

12000.0 pounds zero to full speed first drum

**Braking Method:**

Mechanical

**Drum Surface Design:**

Plain

**Err Default:**

Err default

**Err Default:**

Err default

**Cooling Method:**

Water-air cooled

**Product Name:**

Winch, hydraulic

**Special Features:**

Ipart number breakdown: pd (power drum), 12 (12, 000 lb first layer line pull), c (the model series relating to design changes), spl (), 21 (total gear reduction) 21.00: 1, 064 (hydraulic motor displacement in cubic inches per revolution 6.4 cu in/rev), 02 (drum style). Included: multi-disc brake (spring applied, hydraulically released brake, planetary gearing, full load anchor, brake valve, anti-friction bearings, high efficiency motor. Cast drum and base.

**Type/model Designation:**

Pd12c

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02800