

View Online at <https://aerobasegroup.com/nsn/3950-01-521-0086>

Prime Mover Quantity:

1

Prime Mover Type:

Hydraulic motor

Operation Method:

Powered

Drum Flange To Flange Distance And Location:

13.750 inches first drum err-100

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Style:

Single head

Load Limit At Selected Speed And Drum Location:

12000.0 pounds zero to full speed first drum

Braking Method:

Mechanical

Drum Surface Design:

Plain

Err Default:

Err default

Err Default:

Err default

Cooling Method:

Water-air cooled

Product Name:

Winch, hydraulic

Special Features:

Ipart number breakdown: pd (power drum), 12 (12, 000 lb first layer line pull), c (the model series relating to design changes), spl (), 21 (total gear reduction) 21.00: 1, 064 (hydraulic motor displacement in cubic inches per revolution 6.4 cu in/rev), 02 (drum style). Included: multi-disc brake (spring applied, hydraulically released brake, planetary gearing, full load anchor, brake valve, anti-friction bearings, high efficiency motor. Cast drum and base.

Type/model Designation:

Pd12c

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02800