

View Online at <https://aerobasegroup.com/nsn/3950-01-562-1434>

**Prime Mover Quantity:**

1

**Current Type:**

Dc

**Furnished Items And Quantity:**

1 motor controller and 1 remote control and 1 wire rope

**Environmental Protection:**

Corrosion resistant and fungus resistant and splash proof

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Duty Cycle:**

Intermittent

**Operation Method:**

Powered

**Drum Diameter And Location:**

5.310 inches first drum

**Drum Flange Diameter And Location:**

8.900 inches first drum

**Capstan Spool Mounting Position:**

Horizontal

**Capstan Spool Quantity:**

1

**Travel Rate Per Minute:**

15.0 feet and 16.0 feet and 18.0 feet and 20.0 feet

**Braking Method:**

Electric

**Power Requirement Rating:**

1870.0 watts

**Cooling Method:**

Air to air cooled

**Product Name:**

Dc 3000 lf-24v industrial dc hoist

**Special Features:**

Gear ratio 199: 1; 3-stage planetary gear reduction; 18: 1 cable-to-drum ratio; 8mm wire rope provided; 3000 lb rated load

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02800