## NSN 3950-01-574-2597

Windlass - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3950-01-574-2597

| Prime Mover Quantity:  |
|--|
| 1  |
| Current Type:  |
| Ac   |
| Environmental Protection:                                      |
| Any acceptable   |
| End Application:   |
| Anchor windlass (stbd) onboard 210 ft wmec coast guard vessels |
| Prime Mover Type:  |
| Electric motor   |
| Inclosure Type:  |
| Any acceptable   |
| Duty Cycle:  |
| Continuous   |
| Operation Method:  |
| Powered  |
| Capstan Spool Mounting Position:                               |
| Vertical   |
| Capstan Spool Quantity:  |
| 1  |
| Braking Method:  |
| Electric   |
| Power Requirement Rating:                                      |
| 15.00 horsepower   |
| Cooling Method:  |
| Air to air cooled  |
| Product Name:  |
| Anchor windlass stbd   |
| Voltage In Volts:  |
| 440.0  |
| Phase:   |
| Three  |
| Frequency In Hertz:  |
| 60.0   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |

ı ııg.

A02800