

View Online at <https://aerobasegroup.com/nsn/3950-01-574-6650>

**Current Type:**

Ac

**End Application:**

Anchor windlass; p/n 08001214 port

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Duty Cycle:**

Continuous

**Operation Method:**

Hand

**Capstan Spool Mounting Position:**

Vertical

**Capstan Spool Surface Design:**

Plain

**Braking Method:**

Manual

**Voltage In Volts:**

44.0

**Phase:**

Single

**Special Features:**

Static loa (bitt load) : 110, 000 lb; capstan operating speeds, unloaded: high: 15.87rpm, low: 7.94rpm; hawser size: 5.5 in.Dia nylon or 4.13 in.Aramid; anchor weight: 4, 000lb; rated depth: 30 fathoms; rated speed: 6 fathoms/minute; depth: 120 fathoms; motor power requirement: 440vac, 3 phase, 60-hz; brake power requirement: 440 vac, 1-phase, 60hz; planetary reducer ratio: 26.52: 1; electric brake torque: 330 ft-lb

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A02800