

View Online at <https://aerobasegroup.com/nsn/4010-01-650-8939>

**Diameter:**

0.09375 inches rope

**Lay Method:**

Right regular all layers

**Breaking Strength:**

552.0 pounds

**Core Construction:**

Independent wire rope

**Prefabrication Form:**

Straight

**Product Name:**

Wire rope, flexible, type i (jacketed) , composition a

**Special Features:**

Total o.D. With nylon jacket is 0.15625 inches; type ii wire shall be capable of operating within -65 degree f to +200 degrees f

**Material:**

Plastic polyamide strand covering

**Material Specification:**

Sae-ams-std-66 national std/spec single material response wire rope

**Surface Treatment:**

Zinc or tin wire rope

**Surface Treatment Specification:**

Mil-dtl-83420m government std/spec 1st treatment response and tin over zinc per mil-dtl-83420m government std/spec 2nd treatment response wire rope

**Style Designator:**

7 x 7

**Specification Data:**

81349-mil-dtl-83420/3d government specification

**Specification Or Standard:**

Ii type and a composition

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A082a0

**Mil-std (military Standard):**

Mil-dtl-83420 spec.