

View Online at <https://aerobasegroup.com/nsn/4130-00-089-9064>

Gas For Which Designed:

Refrigerant r-12 and refrigerant r-502

Discharge Flow Rate:

2.800 cubic feet per minute

Cooling System Design:

Single

Compressor Cooling Medium:

Air

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Reciprocating Compressor Design:

Single acting

Cylinder Quantity:

2

Cylinder Arrangement Style:

Vertical design

Stage Quantity:

1

Refrigeration Flow Rate In Tons Per Hour:

0.7

Compressor Speed At Rated Capacity In Rpm:

1750.0

Intake Connection Quantity:

1

Intake Connection Type:

Flared tube

Discharge Connection Quantity:

1

Discharge Connection Type:

Flared tube

Prime Mover Type:

Electric motor

Current Type And Rating In Amps:

5.9 ac

Voltage In Volts And Current Type:

230.0 ac

Temperature Rating Per Function:

130.0 degrees fahrenheit discharge and 65.0 degrees fahrenheit suction

Brake Power Required:

0.750 horsepower

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A026a0