Refrigeration Condenser - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4130-00-289-1335

Media For Which Designed: Freen 12 Shell Material: Copper Head Material: Gumetal Tube Quantity: 48 Water For Which Designed: Sait: Pass Quantity: 6 Tube Material: Nickel copper alloy Tube Effective Length: 6.312 feet Tube File: Not provided Shell Outside Diameter: 8.425 inches Water Connection Type: Flange Water Connection Size: 1.1/2 in. lpa Refrigerant Side Test Minimum Pressure: 200.0 pounds per square inch Water Side Test Minimum Pressure: 200.0 pounds per square inch Water Side Test Minimum Pressure: 201.0 pounds per square inch Water Side Test Minimum Pressure: 202.0 pounds per square inch Water Side Test Minimum Pressure: 21.1/2 in. lpa Refigerant Side Test Minimum Pressure: 22.5.0 pounds per square inch Water Side Test Minimum Retestare Wa	Modio For Which Designed			
Shell Material:CopperHead Material:GumstalGumstalTube Quantity:AaWater For Which Designed:Sal:Pase Quantity:6Tube Effective Length:10.1Kickel copper alloyTube Effective Length:6.312 feetTube Fin:Not providedShell Sumster:8.255 inchesWater Connection Type:FlangeVater Connection Size:1.121 in. IpsRefreent Minimu Pressure:25.0 pounds per square inchWater Schell Minimu Pressure:25.0 pounds per square inchMater Schell Minimu Pressure:26.0 pounds per square inchMater Schell Minimu Pressure:27.0 pounds per square inchMater Schell Minimu Pressure:28.0 pounds per square inchMater Schell Minimu Pressure:29.0 pounds per square inchMater Schell Minim				
CopperHead Material:GummetalTube Quantity:48Water For Which Designed:SattPass Quantity:6Tube Material:Nickel copper alloyTube Effective Length:6.312 featNickel copper alloySuther Effective Length:6.312 featSuber Diameter:8.425 inchesWater Connection Type:FlangeWater Connection Size:1.1/2 in. IpsRefrigent Sile Test Minimum Pressure:30.0 pounds per square inchWater Side Test Minimum Pressure:25.0 pounds per square inchMater Side Test Minimum Pressure:NaNaDifficient Side Test Minimum Pressure:Na <tr< th=""><th></th><th></th><th></th><th></th></tr<>				
Head Material:GunmetalTube Quantity:48Water For Which Designed:SaltPase Quantity:6Tube Material:Nickel copper alloyTube Effective Length:6.312 fedtTube Effective Length:6.312 fedtSubtile Diameter:8.425 inchesWater Connection Type:FlangeVater Connection Size:1.1/2 in, IpsRefrigent Side Test Minimum Pressure:20.0.0 pounds per square inchVater Side Test Minimum Pressure:25.0 pounds per square inchVater Side Test Minimum Pressure:26.0 pounds per square inchVater Side Test Minimum Pressure:27.0 pounds per square inchVater Side Test Minimum Pressure:28.0 pounds per square inchVater Side Test Minimum Pressure:29.0 pounds per square inch20.0 pounds per				
GunmetalTube Quantity:48Water For Which Designed:SattPase Quantity:6Tube Extention:Nickel dooper alloyTube Effective Length:6.312 feetSuber Duritice Diameter:8.425 inchesWater Connection Type:FlangeVater Side Test Minimum Pressure:30.0 pounds per square inchWater Side Test Minimum Pressure:25.0 pounds per square inchMaintingFig:NaDifferie:NaMaintingSide Test Minimum Pressure:NaSide Test Minimum Pressure:Side Test Minimum Pressure:Side Test Minimum Pressure:NaSide Test Minimum Pressure:Side Test Minimum Pressure:				
Tube Quantity: 48 Water For Which Designed: Sait Pass Quantity: Pass Quantity: 6 Tube Material: Nickel copper alloy Tube Effective Length: 6.312 feet Tube Fin: Not provided Shell Outside Diameter: 8.625 inches Water Connection Type: Flange Patrigerant Side Test Minimum Pressure: 1.1/2 in. lps Refrigerant Side Test Minimum Pressure: 200 pounds per square inch Water Side Test Minimum Pressure: 205.0 pounds per square inch Water Side Test Minimum Pressure: 205.0 pounds per square inch Water Side Test Minimum Pressure: 205.0 pounds per square inch Water Side Test Minimum Pressure: 201.0 for Measure:				
48 Water For Which Designed: Sait Pass Quantity: Pass Quantity: 6 Tube Material: Nickel copper alloy Tube Effective Length: 6.312 feat 7 Jube Fin: Not provided Shell Outside Diameter: 8.625 inches Water Connection Type: Flange Water Connection Size: 1.1/2 in. lps Refrigerant Side Test Minimum Pressure: 200.0 pounds per square inch Water Side Test Minimum Pressure: 205.0 pounds per square inch Water Side Test Minimum Pressure: 205.0 pounds per square inch Water Side Test Minimum Pressure: 205.0 pounds per square inch Water Side Test Minimum Pressure: 205.0 pounds per square inch Water Side Test Minimum Pressure: Vater Side Test Minimum Pressure: Vater Side Test Minimum Pressure: Part Heit: Nature Fing: Nature Side Test Minimum Pressure: Side Test Minimum Pressure:				
Water For Which Designed: Salt Pass Quantity: Pass Quantity: 6 Tube Material: Nickel copper alloy Tube Effective Length: 6.312 feet Tube Fin: Not provided Shell Outside Diameter: 8.625 inches Water Connection Type: Flang Water Connection Size: 1.1/2 in. lps Refrigerant Side Test Minimum Pressure: 200.0 pounds per square inch Water Side Test Minimum Pressure: 25.0 pounds per square inch Via Dint of Measure: - re Pister Side Test Minimum Pressure: 25.0 pounds per square inch Mater Side Test Minimum Pressure: 25.0 pounds per square inch Mater Side Test Minimum Pressure: 25.0 pounds per square inch Na Dint of Measure: - Pister Side Test Minimum Pressure: Side Test Minimum Pressure: Side Test Minimum Pressure: Side Test Minimum Pressure:				
SaltPass Quantity:6Tube Material:Nickel copper alloyTube Effective Length:6.312 feetTube Fin:Not providedShell Outside Diameter:8.625 inchesWater Connection Type:FlangeVater Connection Size:1.1/2 in. lpsRefrigerant Side Test Minimum Pressure:200.0 pounds per square inchWater Side Test Minimum Pressure:25.0 pounds per square inchMarkMarkInformation:N/aShelf Life:N/aFin:Fin:NaFin:NaShelf Life:NaShelf Life:NaSint Side Test Minimum Pressure:Sint Side Test Minimum Pressure:NaShelf Life:NaFin:Fin:Sint Side Test Minimum Pressure:Sint Side Test Minimum Pressure:				
Pass Quantity: 6 Tube Material: Nickal copper alloy Tube Effective Length: 6.312 feet Tube Fin: Not provided Shell Outside Diameter: 8.625 inches Water Connection Type: Flange Vater Connection Size: 1.1/2 in.lps Refrigerant Side Test Minimum Pressure: 300.0 pounds per square inch Vater Side Test Minimum Pressure: 25.0 pounds per square inch Shelf Life: N/a Dit Of Measure: Imiliarization: No Fig:				
6 Tube Material: Nickel copper alloy Tube Effective Length: 6.312 feet Tube Fin: Not provided Shell Outside Diameter: 8.625 inches 8.625 inches Mater Connection Type: Flange Flange Mater Connection Size: 1.1/2 in. lps Refrigerant Side Test Minimum Pressure: 300.0 pounds per square inch Mater Side Test Minimum Pressure: 25.0 pounds per square inch Shelf Life: Na Shelf Life: Na Fig:				
Tube Material:Nickel copper alloyTube Effective Length:6.312 feetTube Fin:Not providedShell Outside Diameter:8.625 inchesWater Connection Type:FlangeWater Connection Size:1.1/2 in. lpsRefrigerant Side Test Minimum Pressure:30.0 pounds per square inchWater Side Test Minimum Pressure:25.0 pounds per square inchMater Side Test Minimum Pressure:25.0 pounds per square inchNaInt Of Measure:NaFig:Na				
Nickel copper alloyTube Effective Length:6.312 feetTube Fin:Not providedShell Outside Diameter:8.625 inchesWater Connection Type:FlangeVater Connection Size:1.1/2 in. lpsRefrigerant Side Test Minimum Pressure:300.0 pounds per square inchWater Side Test Minimum Pressure:25.0 pounds per square inchShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:				
Tube Effective Length:6.312 feetFube Fin:Not providedShell Outside Diameter:8.625 inchesWater Connection Type:FlangeWater Connection Size:1.1/2 in. lpsRefrigerant Side Test Minimum Pressure:300.0 pounds per square inchWater Side Test Minimum Pressure:252.0 pounds per square inchShelf Life:NaDir of Measure:Fing:NoFing:Fing:				
6.312 feetTube Fin:Not providedShell Outside Diameter:8.625 inchesWater Connection Type:FlangeWater Connection Size:1-1/2 in. lpsRefrigerant Side Test Minimum Pressure:300.0 pounds per square inchWater Side Test Minimum Pressure:225.0 pounds per square inchShelf Life:N/aDenilitarization:Fing:NaFing:Fing:				
Tube Fin:Not providedNot providedShell Outside Diameter:8.625 inchesWater Connection Type:FlangeWater Connection Size:1-1/2 in. lpsRefrigerant Side Test Minimum Pressure:300.0 pounds per square inchWater Side Test Minimum Pressure:252.0 pounds per square inchShelf Life:N/aInit of Measure:				
Not provided Shell Outside Diameter: 8.625 inches Water Connection Type: Flange Water Connection Size: 1-1/2 in. lps Refrigerant Side Test Minimum Pressure: 300.0 pounds per square inch Water Side Test Minimum Pressure: 25.0 pounds per square inch Shelf Life: N/a Init Of Measure: Demiltarization: No Fig:	6.312 feet			
Shell Outside Diameter:8.625 inchesWater Connection Type:FlangeWater Connection Size:1-1/2 in. lpsRefrigerant Side Test Minimum Pressure:300.0 pounds per square inchWater Side Test Minimum Pressure:225.0 pounds per square inchShelf Life:N/aDrint Of Measure:Snot Side Test Minimum Pressure:Int Of Measure:Frig:NoFig:	Tube Fin:			
8.625 inches Water Connection Type: Flange Water Connection Size: 1-1/2 in. lps Refrigerant Side Test Minimum Pressure: 300.0 pounds per square inch Water Side Test Minimum Pressure: 225.0 pounds per square inch Shelf Life: N/a Unit Of Measure: Floig:	Not provided			
Water Connection Type:FlangeWater Connection Size:1-1/2 in. lpsRefrigerant Side Test Minimum Pressure:300.0 pounds per square inchWater Side Test Minimum Pressure:225.0 pounds per square inchShelf Life:N/aInit Of Measure:Demilitarization:NoFig:	Shell Outside Diameter:			
Flange Water Connection Size: 1-1/2 in. lps Refrigerant Side Test Minimum Pressure: 300.0 pounds per square inch Water Side Test Minimum Pressure: 225.0 pounds per square inch Shelf Life: N/a Via Dint Of Measure: Fig:	8.625 inches			
Water Connection Size:1-1/2 in. lpsRefrigerant Side Test Minimum Pressure:300.0 pounds per square inchWater Side Test Minimum Pressure:225.0 pounds per square inchShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	Water Connection Type:			
1-1/2 in. lps Refrigerant Side Test Minimum Pressure: 300.0 pounds per square inch Water Side Test Minimum Pressure: 225.0 pounds per square inch Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Flange			
Refrigerant Side Test Minimum Pressure:300.0 pounds per square inchWater Side Test Minimum Pressure:225.0 pounds per square inchShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Water Connection Size:			
300.0 pounds per square inch Water Side Test Minimum Pressure: 225.0 pounds per square inch Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1-1/2 in. lps			
Water Side Test Minimum Pressure:225.0 pounds per square inchShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Refrigerant Side Test Minimum Pressu	e:		
225.0 pounds per square inch Shelf Life: N/a Unit Of Measure: Demilitarization: No	300.0 pounds per square inch			
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Water Side Test Minimum Pressure:			
N/a Unit Of Measure: Demilitarization: No Fiig:	225.0 pounds per square inch			
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:			
 Demilitarization: No Fiig:	N/a			
Demilitarization: No Fiig:	Unit Of Measure:			
No Fiig:				
Fiig:	Demilitarization:			
	No			
T240-a	Fiig:			
	T240-a			