NSN 4130-00-374-3042

Piston Connecting Rod - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4130-00-374-3042

| Cross Sectional Shape: |
|--|
| Flat type |
| Fabrication Method: |
| Cast |
| Shaft Connecting End Style: |
| Press sleeve |
| End Thickness: |
| 0.625 inches |
| Edge Radius: |
| 0.406 inches |
| End Hole Inside Diameter: |
| 0.265 inches |
| Piston Connecting End Bearing: |
| Not included |
| Piston Connecting End Lubrication Drill Feature: |
| Included |
| Piston Connecting End Lubrication Method: |
| Full forced-feed |
| Shaft Connecting End Bearing: |
| Included |
| Shaft Connecting End Hole Inside Diameter: |
| 1.500 inches |
| Shaft Connecting End Edge Radius: |
| 1.875 inches |
| Shaft Connecting End Thickness: |
| 0.625 inches |
| Shaft Connecting End Bearing Replaceability: |
| Replaceable |
| Shaft Connecting End Lubrication Drill Feature: |
| Included |
| Shaft Connecting End Lubrication Method: |
| Forced-feed |
| Center To Center Effective Length: |
| 4.250 inches |
| Body Width At Piston Connecting End: |
| 0.625 inches |
| Body Width At Shaft Connecting End: |
| 1.000 inches |
| Body Thickness At Piston Connecting End: |
| 0.500 inches |
| Body Thickness At Shaft Connecting End: |
| 0.500 inches |

NSN 4130-00-374-3042

Piston Connecting Rod - Page 2 of 2



| Piston | End | Connection | Style |
|--------|-----|------------|-------|
| riston | Ena | Connection | Style |

Small engine and automotive standard

Material:

Iron, cast

Material:

Iron cast

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T267-d