

View Online at <https://aerobasegroup.com/nsn/4130-00-393-4889>

Casehardening Indicator:

Not casehardened

Hole Diameter:

Between 0.171 inches and 0.176 inches

Overall Length:

6.141 inches

Flange Thickness:

Between 0.750 inches and 0.751 inches

Bore Diameter:

Between 3.250 inches and 3.2515 inches

Body Outside Diameter:

3.906 inches

Metallic Hardness Rating:

170.0 brinell standard and 210.0 brinell standard

Flange Outside Diameter:

Between 5.1235 inches and 5.1245 inches

Design Type:

Dry

Row Quantity:

1

Bottom Chamfer Angle In Deg:

30.0

Bottom Chamfer Length:

0.500 inches

Valve Recess:

Included

Top Inside Chamfer:

Not included

Bottom Inside Chamfer:

Included

Top Intake Port:

Not included

Intake Hole:

Included

Hole Center To Center Distance Between Rows:

Any acceptable

Hole Quantity Per Row:

6

Distance From Top To Center Of First Row:

0.156 inches

Special Features:

Six holes around top of flange

Material:

Iron, qq-i-652-canceled

Material:

Iron cast uns f11401 or iron cast uns f11701 or iron cast uns f12101 or iron cast uns f12401 or iron cast uns f12801 or iron cast uns f13101
or iron cast uns f13501 or iron cast uns f13801 or iron cast uns f14101

Style Designator:

Dry, flanged, relieved

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T267-b