NSN 4130-00-935-1637

Refrigeration Compressor Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4130-00-935-1637 **Duty Cycle In Percent:** 100 **Gas For Which Designed:** Refrigerant r-12 **Discharge Flow Rate:** Not rated **Discharge Pressure:** 126.600 pounds per square inch gage **Cooling System Design:** Mixed **Compressed Gas Cooling Medium:** Salt water **Compressor Cooling Medium:** Refrigerant **Prime Mover Cooling Medium:** Air **Unloader Type:** Automatic **Brake Horsepower Required:** 74.000 **Mounting Type:** Base **Reciprocating Compressor Design:** Single acting **Cylinder Quantity:** 12 **Cylinder Arrangement Style:** "w" design **Stage Quantity:** Refrigeration Flow Rate In Tons Per Hour: 55.0 **Suction Pressure:** 30.0 pounds per square inch **Compressor Speed At Rated Capacity In Rpm:** 1750.0 **Intake Connection Quantity:** 1 **Intake Connection Type:**

Square flange

Discharge Connection Quantity:

1

NSN 4130-00-935-1637

Refrigeration Compressor Unit - Page 2 of 2



| Discharge Connection Type: |
|--|
| Round flange |
| Prime Mover Type: |
| Electric motor |
| Current Type And Rating In Amps: |
| 91.0 ac |
| Voltage In Volts And Current Type: |
| 440.0 ac |
| Tempurature Rating Per Function: |
| 105.0 degrees fahrenheit discharge and 32.4 degrees fahrenheit suction |
| Brake Power Required: |
| 74.000 horsepower |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Reference Number Differentiating Characteristics: |
| As differentiated by reply to pac aaye |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A026a0 |
| |