Refrigeration Condenser - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4130-01-514-6573

Overall Length:8.500 inchesOverall Width:8.000 inchesMedia For Which Designed:Chilled waterEnd Application:Cis-10n drinking dispenserFan Quantity:1Water For Which Designed:FreshCondensing Surface Area:0.476 square feetTube Fin:ProvidedRefrigerant Inlet Connection Quantity:1Refrigerant Inlet Connection Type:Copper tubeRefrigerant Inlet Connection Type:Copper tubeColling Type:AirPratlelVoltage In Volts And Current Type:20.02 as and 240.0 acSpecial Features:A copper aluminum condenser that is double row 8 x 8.5inNet If it:NaFing:NaFing:NaFing:NaSpecial Features:NaFing:Special Features:NaSpecial Features:<	New Online at https://aerobasegroup.com/hsil/4150-01-514-0575	
Overall Width:8.000 inchesMedia For Which Designed:Chilled waterEnd Application:Cits-10n drinking dispenserFan Quantity:1Mater For Which Designed:FreshCondensing Surface Area:0.476 square feetTube Fin:ProvidedRefrigerant Inlet Connection Quantity:1Refrigerant Inlet Connection Quantity:1Refrigerant Inlet Connection Quantity:1Refrigerant Outlet Connection Quantity:1Refrigerant Outlet Connection Type:Copper tubeCopper tubeCopper tubeCopper tubeCould Type:20.0 ac and 240.0 acSpecial Features:A copper aluminum condenser that is double row 8 x 8.5inShell Itie:NaUnit of Measure:Condensure:Pomilitarization:NaFig:Fig:	Overall Length:	
8.000 inches         Media For Which Designed:         Chilled water         End Application:         Cifs-10n drinking dispenser         Fan Quantity:         1         Water For Which Designed:         Fresh         Condensing Surface Area:         0.476 square feet         Tube Fin:         Provided         Refrigerant Inlet Connection Quantity:         1         Refrigerant Inlet Connection Quantity:         1         Refrigerant Outlet Connection Quantity:         1         Refrigerant Outlet Connection Quantity:         1         Refrigerant Outlet Connection Type:         Copper tube         Copper tube         Cooling Type:         Air         Parallel         Voltage In Volts And Current Type:         22.0.0 ac and 240.0 ac         Speir Life:         Na         Unit Of Measure:         Va         Unit of Measure:         Paralle         Na         Diff Life:         Na         Diff Of Measure:         Paralle         Na	8.500 inches	
Media For Which Designed:         Chilled water         End Application:         Cits-10n drinking dispenser         Fan Quantity:         1         Water For Which Designed:         Fresh         Condensing Surface Area:         0.476 square feet         Tube Fin:         Provided         Refrigerant Inlet Connection Quantity:         1         Refrigerant Inlet Connection Type:         Copper tube         Refrigerant Outlet Connection Type:         Copper tube         Cooling Type:         Air         Pratl Direction:         Parallel         Voltage In Volts And Current Type:         22.0. ac and 240.0 ac         Special Features:         A copper aluminum condenser that is double row 8 x 8.5in         Shelf Life:         Na         Unit Of Measure:         -         Penilitarization:         Na         Fig:	Overall Width:	
Chilled water End Application: Cfs-10n drinking dispenser Fan Quantity: 1 Water For Which Designed: Fresh Condensing Surface Area: 0.476 Square feet Cube Fin: Provided Refrigerant Inlet Connection Quantity: 1 Refrigerant Inlet Connection Type: Copper tube Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Type: Copper tube Copper tube Cooling Type: Air Draft Direction: Paralle Voltag In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Sheff Life: Na Unit Of Measure:  Paralle Na Denilitarization: No	8.000 inches	
End Application: Cis-10n drinking dispenser Fan Quantity: 1  Yater For Which Designed: Fresh Condensing Surface Area: 0.476 square feet Cubefin: Provided Refrigerant Inlet Connection Quantity: 1 Refrigerant Inlet Connection Type: Copper tube Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Type: Copper tube Cooling Type: Air Draft Direction: Parallel Voltag In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Sheff Life: Na Cuit Of Measure: Demilitarization: No Fig:	Media For Which Designed:	
Citerior         Fran Quantity:         1         Water For Which Designed:         Fresh         Condensing Surface Area:         0.476 square feet         Tube Fin:         Provided         Refrigerant Inlet Connection Quantity:         1         Refrigerant Inlet Connection Quantity:         1         Refrigerant Outlet Connection Quantity:         1         Refrigerant Outlet Connection Type:         Copper tube         Refrigerant Outlet Connection Type:         Copper tube         Copper tube         Cooling Type:         Air         Draft Direction:         Parallel         Voltage In Volts And Current Type:         220.0 ac and 240.0 ac         Special Features:         A copper aluminum condenser that is double row 8 x 8.5in         Shelf Life:         N/a         Unit Of Measure:         -         Perilitarization:         No         Fig:	Chilled water	
Fan Quantity:         1         Water For Which Designed:         Fresh         Condensing Surface Area:         0.476 square feet         Tube Fin:         Provided         Refrigerant Inlet Connection Quantity:         1         Refrigerant Inlet Connection Type:         Copper tube         Refrigerant Outlet Connection Type:         Copper tube         Cooling Type:         Air         Draft Direction:         Parallel         Voltage In Volts And Current Type:         220.0 ac and 240.0 ac         Special Features:         A copper aluminum condenser that is double row 8 x 8.5in         Shelf Life:         N/a         Unit Of Measure:         -         Pemilitarization:         No         Fig:	End Application:	
1         Water For Which Designed:         Fresh         Condensing Surface Area:         0.476 square feet         Tube Fin:         Provided         Refrigerant Inlet Connection Quantity:         1         Refrigerant Inlet Connection Type:         Copper tube         Refrigerant Outlet Connection Quantity:         1         Refrigerant Outlet Connection Type:         Copper tube         Copper tube         Copper tube         Coling Type:         Air         Parallel         Votage In Volts And Current Type:         220.0 ac and 240.0 ac         Special Features:         A copper aluminum condenser that is double row 8 x 8.5in         Sheff Life:         Na         Unit Of Measure:            Parallel         Point Marker         Special Features:         Na         Duff Of Measure:            Parallel         Nator         Special Features:         Na         Diff Life:         Na         Diff Measure: </td <td>Cfs-10n drinking dispenser</td> <td></td>	Cfs-10n drinking dispenser	
Water For Which Designed:         Fresh         Condensing Surface Area:         0.476 square feet         Tube Fin:         Provided         Refrigerant Inlet Connection Quantity:         1         Refrigerant Inlet Connection Type:         Copper tube         Refrigerant Outlet Connection Quantity:         1         Refrigerant Outlet Connection Type:         Copper tube         Copper tube         Coling Type:         Air         Draft Direction:         Parallel         Voltage In Volts And Current Type:         220.0 ac and 240.0 ac         Special Features:         A copper aluminum condenser that is double row 8 x 8.5in         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Fan Quantity:	
Fresh   Condensing Surface Area:   0.476 square feet   Tube Fin:   Provided   Refrigerant Inlet Connection Quantity:   1   Refrigerant Inlet Connection Type:   Copper tube   Refrigerant Outlet Connection Quantity:   1   Refrigerant Outlet Connection Quantity:   1   Refrigerant Outlet Connection Type:   Copper tube   Copper tube   Copper tube   Copper tube   Coling Type:   Air   Draft Direction:   Parallel   Voltage In Volts And Current Type:   220.0 ac and 240.0 ac   Special Features:   A copper aluminum condenser that is double row 8 x 8.5in   Shelf Life:   N/a   Unit Of Measure:       Demilitarization:   No   Fig:	1	
Condensing Surface Area: 0.476 square feet Tube Fin: Provided Refrigerant Inlet Connection Quantity: 1 Refrigerant Inlet Connection Type: Copper tube Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Type: Copper tube Cooling Type: Air Draft Direction: Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure:  Demilltarization: No Fig:	Water For Which Designed:	
0.476 square feet Tube Fin: Provided Refrigerant Inlet Connection Quantity: 1 Refrigerant Inlet Connection Type: Copper tube Refrigerant Outlet Connection Type: Copper tube Cooling Type: Air Draft Direction: Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Fresh	
Tube Fin: Provided Refrigerant Inlet Connection Quantity: 1 Refrigerant Inlet Connection Type: Copper tube Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Type: Copper tube Cooling Type: Air Draft Direction: Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Sheff Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Condensing Surface Area:	
Provided Provided Refrigerant Inlet Connection Quantity: 1 Refrigerant Inlet Connection Type: Copper tube Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Type: Copper tube Cooling Type: Copper tube Cooling Type: Air Draft Direction: Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	0.476 square feet	
Refrigerant Inlet Connection Quantity:   1   Refrigerant Inlet Connection Type:   Copper tube   Refrigerant Outlet Connection Type:   1   Refrigerant Outlet Connection Type:   Copper tube   Copper tube   Cooling Type:   Air   Draft Direction:   Parallel   Voltage In Volts And Current Type:   220.0 ac and 240.0 ac   Special Features:   A copper aluminum condenser that is double row 8 x 8.5in   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Tube Fin:	
1         Refrigerant Inlet Connection Type:         Copper tube         Refrigerant Outlet Connection Quantity:         1         Refrigerant Outlet Connection Type:         Copper tube         Cooling Type:         Air         Draft Direction:         Parallel         Voltage In Volts And Current Type:         220.0 ac and 240.0 ac         Special Features:         A copper aluminum condenser that is double row 8 x 8.5in         Shelf Life:         N/a         Unit Of Measure:         -         -         Demilitarization:         No         Fig:	Provided	
Refrigerant Inlet Connection Type:   Copper tube   Refrigerant Outlet Connection Quantity:   1   Refrigerant Outlet Connection Type:   Copper tube   Cooling Type:   Air   Draft Direction:   Parallel   Voltage In Volts And Current Type:   220.0 ac and 240.0 ac   Special Features:   A copper aluminum condenser that is double row 8 x 8.5in   Shelf Life:   N/a   Unit Of Measure:       Demilitarization:   No   Fig:	Refrigerant Inlet Connection Quantity:	
Copper tube Refrigerant Outlet Connection Quantity: 1 Refrigerant Outlet Connection Type: Copper tube Cooling Type: Air Draft Direction: Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	1	
Refrigerant Outlet Connection Quantity:   1   Refrigerant Outlet Connection Type:   Copper tube   Cooling Type:   Air   Draft Direction:   Parallel   Voltage In Volts And Current Type:   220.0 ac and 240.0 ac   Special Features:   A copper aluminum condenser that is double row 8 x 8.5in   Shelf Life:   N/a   Unit Of Measure:   -   Demilitarization:   No   Fig:	Refrigerant Inlet Connection Type:	
1         Refrigerant Outlet Connection Type:         Cooper tube         Cooling Type:         Air         Draft Direction:         Parallel         Voltage In Volts And Current Type:         220.0 ac and 240.0 ac         Special Features:         A copper aluminum condenser that is double row 8 x 8.5in         Shelf Life:         N/a         Unit Of Measure:               Pemilitarization:         No         Fig:	Copper tube	
Refrigerant Outlet Connection Type:   Copper tube   Cooling Type:   Air   Draft Direction:   Parallel   Voltage In Volts And Current Type:   220.0 ac and 240.0 ac   Special Features:   A copper aluminum condenser that is double row 8 x 8.5in   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Refrigerant Outlet Connection Quantity:	
Copper tube Cooling Type: Air Draft Direction: Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1	
Cooling Type: Air Draft Direction: Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Refrigerant Outlet Connection Type:	
Air Draft Direction: Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Copper tube	
Draft Direction:ParallelVoltage In Volts And Current Type:220.0 ac and 240.0 acSpecial Features:A copper aluminum condenser that is double row 8 x 8.5inShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Cooling Type:	
Parallel Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Air	
Voltage In Volts And Current Type: 220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Draft Direction:	
220.0 ac and 240.0 ac Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Parallel	
Special Features: A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Voltage In Volts And Current Type:	
A copper aluminum condenser that is double row 8 x 8.5in Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	220.0 ac and 240.0 ac	
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Special Features:	
N/a Unit Of Measure:  Demilitarization: No Fiig:	A copper aluminum condenser that is double row 8 x 8.5in	
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
T240-a	Fiig:	
	T240-a	