NSN 4140-00-007-4578

Vaneaxial Fan - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4140-00-007-4578

| Stage Quantity: |
|---|
| 1 |
| Speed Adjustments: |
| Single speed |
| Diameter: |
| 7.120 inches |
| Length: |
| 10.500 inches |
| Flow Direction: |
| Inward |
| Ambient Tempurature At Full Rated Power: |
| -25.0 degrees fahrenheit and 105.0 degrees fahrenheit |
| Operating Speed At Rated Capacity In Rpm: |
| 3450.0 |
| Electrical Connection Type: |
| Wire lead |
| Static Pressure At Specificationified Air Flow Rate: |
| 1.7 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 16 unthreaded hole |
| Rotation Direction For Which Designed: |
| Clockwise |
| Air Flow Rate: |
| 550.0 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 208.0 ac |
| Prime Mover Power Rating: |
| 0.330 horsepower |
| Housing Inside Diameter: |
| 7.125 inches |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Aluminum |
| |

NSN 4140-00-007-4578

Vaneaxial Fan - Page 2 of 2



Quantity:

2

Surface Treatment:

Zinc and anodize

Surface Treatment Specification:

Mil-a-8625 military standard single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.