

View Online at <https://aerobasegroup.com/nsn/4140-00-012-3506>

Speed Adjustments:

Single speed

Width:

3.250 inches

Length:

3.820 inches

Environmental Protection:

Humidity proof and shock proof and vibration proof and salt spray resistant

Ambient Temperature At Full Rated Power:

0.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5500.0

Electrical Connection Type:

Terminal block

Outlet Inside Diameter:

1.250 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 threaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

27.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

21.5 watts

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Single

Special Features:

Positioning when mtg determines discharge blast @direction, class a insulation motor windings

Frequency In Hertz:

400.0

Height:

3.940 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, round outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0