

View Online at <https://aerobasegroup.com/nsn/4140-00-015-6024>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

3.530 inches

Length:

4.469 inches

Operating Speed At Rated Capacity In Rpm:

3350.0

Electrical Connection Type:

Terminal block

Outlet Inside Width:

1.500 inches

Outlet Inside Height:

1.781 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 clamp and 6 unthreaded hole and 4 threaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

33.0 cubic feet per minute

Outlet Location:

Bottom and top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.016 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Fan dim. Do not include 4.93 in. Dia, 0.92 in. Deep bellmouth inlet cone, optional mtg by @bellmouth cone, duct clamp or tapped holes in motor flats permits alternate discharge blast directions, class a insulation motor windings

Frequency In Hertz:

50.0 and 60.0

Height:

4.812 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0