

View Online at <https://aerobasegroup.com/nsn/4140-00-018-6535>

Speed Adjustments:

Single speed

Length:

3.500 inches

Flow Direction:

Outward

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-30.0 degrees celsius and 60.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1400.0 and 1650.0

End Application:

W/s: missile, air-to-air, phoenix (aim-54); helicopter, carrier based asw, sh-60f; missile, all-weather antiship, harpoon (agm-84); missile, advanced medium range air-to-air (amraam)aim120a; deep submergence systems programs (dssp); support equipment, mx peacekeeper missile; shipboard material handling equipment (mhe); helicopter, uscg search and rescue, hh-60j; helicopter, search and rescue, hh-60h

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

8 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

Between 455.0 cubic feet per minute and 550.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

65.0 watts

Housing Inside Diameter:

Between 9.658 inches and 9.678 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Material:

Aluminum housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0