

View Online at <https://aerobasegroup.com/nsn/4140-00-020-8930>

Speed Adjustments:

Single speed

Width:

3.430 inches

Length:

3.660 inches

Operating Speed At Rated Capacity In Rpm:

3400.0

Electrical Connection Type:

Terminal block

Outlet Inside Width:

1.406 inches

Outlet Inside Height:

1.468 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 threaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

21.0 cubic feet per minute

Outlet Location:

Bottom and top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.012 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Single

Special Features:

Designed for mtg w/motor shaft in any position, mtg by outlet flange or tapped holes in motor flats permits adjustable discharge blast direction, class f insulation motor windings

Frequency In Hertz:

50.0 and 60.0

Height:

3.880 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0