

View Online at <https://aerobasegroup.com/nsn/4140-00-022-1176>

**Speed Adjustments:**

Single speed

**Length:**

Between 5.938 inches and 6.062 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Dustproof and fungus resistant and moisture resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

0.0 degrees celsius and 50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3150.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

115.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.054 horsepower

**Housing Inside Diameter:**

4.125 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

2 fans mechanically assembled back to back; air flow rate at 65 cfm and 3 in. Water static pressure; 4.688 in. Sq flange both ends venturi tube

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Plastic polycarbonate blade

**Surface Treatment:**

Enamel blade

**Style Designator:**

Fixed

**Test Data Document:**

49956-497885-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0