

View Online at <https://aerobasegroup.com/nsn/4140-00-023-4442>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

6.472 inches

**Length:**

4.501 inches

**Ambient Temperature At Full Rated Power:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Electrical Connection Type:**

Wire lead

**Outlet Inside Diameter:**

0.880 inches

**Static Pressure At Specificationified Air Flow Rate:**

14.3 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 base and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking and safety impeller guard

**Air Flow Rate:**

26.500 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac or 200.0 ac

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular up

**Phase:**

Three

**Special Features:**

W/grounded neutral lead, nameplate shall not contain any identification of u. S. Government ownership

**Frequency In Hertz:**

320.0 and 495.0

**Height:**

6.000 inches

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Chromate housing outside and lacquer housing outside

**Style Designator:**

Fixed, round outlets

**Test Data Document:**

36659-644786-7 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0