

View Online at <https://aerobasegroup.com/nsn/4140-00-023-4442>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

6.472 inches

Length:

4.501 inches

Ambient Temperature At Full Rated Power:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Electrical Connection Type:

Wire lead

Outlet Inside Diameter:

0.880 inches

Static Pressure At Specificationified Air Flow Rate:

14.3 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 base and 4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking and safety impeller guard

Air Flow Rate:

26.500 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 ac or 200.0 ac

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular up

Phase:

Three

Special Features:

W/grounded neutral lead, nameplate shall not contain any identification of u. S. Government ownership

Frequency In Hertz:

320.0 and 495.0

Height:

6.000 inches

Material:

Aluminum

Quantity:

1

Surface Treatment:

Chromate housing outside and lacquer housing outside

Style Designator:

Fixed, round outlets

Test Data Document:

36659-644786-7 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0