

View Online at <https://aerobasegroup.com/nsn/4140-00-026-5437>

**Speed Adjustments:**

Single speed

**Width:**

5.100 inches

**Length:**

4.970 inches

**Environmental Protection:**

Explosion proof and humidity proof and moisture resistant and salt spray resistant and shock proof and vibration proof

**Operating Speed At Rated Capacity In Rpm:**

8500.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

2.130 inches

**Outlet Inside Height:**

2.040 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

150.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.415 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Height:**

6.010 inches

**Material:**

Steel housing

**Surface Treatment:**

Chromate zinc housing and enamel housing

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0