

View Online at <https://aerobasegroup.com/nsn/4140-00-027-5150>

Speed Adjustments:

Single speed

Width:

5.812 inches

Length:

5.250 inches

Environmental Protection:

Corrosion resistant and moisture resistant and vibration proof

Operating Speed At Rated Capacity In Rpm:

2900.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

2.188 inches

Outlet Inside Height:

2.188 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

75.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Positioning when @mtg by outlet flange determines discharge blast direction

Frequency In Hertz:

60.0

Height:

5.188 inches

Material:

Aluminum

Style Designator:

Fixed, rectangular outlets

Reference Number Differentiating Characteristics:

As differentiated by the impeller rotation direction requirement

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0