NSN 4140-00-036-5700

Tubeaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-036-5700 **Speed Adjustments:** Single speed Length: 1.500 inches Flow Direction: Inward **Ambient Tempurature At Full Rated Power:** 72.0 degrees celsius **Operating Speed At Rated Capacity In Rpm:** 2700.0 and 3200.0 **Electrical Connection Type: Terminal** Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 2 flange **Rotation Direction For Which Designed:** Counterclockwise Air Flow Rate: Between 88.0 cubic feet per minute and 105.0 cubic feet per minute **Voltage In Volts And Current Type:** 115.0 ac **Prime Mover Power Rating:** 0.019 horsepower **Housing Inside Diameter:** 4.500 inches **Prime Mover Drive Shaft Bearing Type:** Sleeve Phase: Single Frequency In Hertz: 50.0 and 60.0 Material:

Plastic phenolic housing **Style Designator:** Fixed

NSN 4140-00-036-5700

Tubeaxial Fan - Page 2 of 2



| Test | Data | Docum | ent |
|------|------|-------|-----|
|------|------|-------|-----|

| 98230-0n169592-1 drawing (this | is the basic governing drawing, | such as a contractor drawing, | original equipment manufacturer drawing, |
|-----------------------------------|---------------------------------|---------------------------------|--|
| etc.; excludes any specification, | standard or other document that | at may be referenced in a basic | governing drawing) |

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0