

View Online at <https://aerobasegroup.com/nsn/4140-00-036-5700>

**Speed Adjustments:**

Single speed

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Ambient Temperature At Full Rated Power:**

72.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2700.0 and 3200.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

Between 88.0 cubic feet per minute and 105.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.019 horsepower

**Housing Inside Diameter:**

4.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Sleeve

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Plastic phenolic housing

**Style Designator:**

Fixed

**Test Data Document:**

98230-0n169592-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0