

View Online at <https://aerobasegroup.com/nsn/4140-00-043-1981>

Speed Adjustments:

Single speed

Length:

Between 1.422 inches and 1.516 inches

Flow Direction:

Outward

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

21000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Clockwise and counterclockwise

Air Flow Rate:

16.000 cubic feet per minute

Voltage In Volts And Current Type:

55.0 ac

Prime Mover Power Rating:

0.031 horsepower

Housing Inside Diameter:

Between 1.552 inches and 1.572 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

800.0

Material:

Aluminum

Surface Treatment:

Anodize

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0