

View Online at <https://aerobasegroup.com/nsn/4140-00-052-4815>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

1.859 inches

**Length:**

1.470 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Humidity proof and shock proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

19000.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

54.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.056 horsepower

**Housing Inside Diameter:**

1.890 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

2.0 in. Sq flange w/hole ea corner at discharge end of venturi tube

**Frequency In Hertz:**

380.0 and 420.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0