

View Online at <https://aerobasegroup.com/nsn/4140-00-052-4815>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

1.859 inches

Length:

1.470 inches

Flow Direction:

Outward

Environmental Protection:

Humidity proof and shock proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

19000.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

54.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.056 horsepower

Housing Inside Diameter:

1.890 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

2.0 in. Sq flange w/hole ea corner at discharge end of venturi tube

Frequency In Hertz:

380.0 and 420.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0