

View Online at <https://aerobasegroup.com/nsn/4140-00-056-3904>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

4.750 inches

Length:

5.000 inches

Flow Direction:

Inward

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-20.0 degrees celsius and 60.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11200.0

Electrical Connection Type:

Terminal block and wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 12 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

350.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.400 horsepower

Housing Inside Diameter:

5.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Magnesium

Quantity:

1

Surface Treatment:

Chromate zinc and lacquer

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0