

View Online at <https://aerobasegroup.com/nsn/4140-00-056-9448>

**Speed Adjustments:**

Single speed

**Width:**

2.781 inches

**Length:**

2.906 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Humidity proof and shock proof

**Ambient Temperature At Full Rated Power:**

-18.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3300.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

55.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.012 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Height:**

4.500 inches

**Material:**

Aluminum

**Surface Treatment:**

Anodize blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0