

View Online at <https://aerobasegroup.com/nsn/4140-00-059-7575>

Speed Adjustments:

Single speed

Length:

2.312 inches

Flow Direction:

Inward

Environmental Protection:

Weatherproof

Ambient Temperature At Full Rated Power:

-65.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

22000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking and radio interference shielding

Air Flow Rate:

162.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

135.0 watts

Housing Inside Diameter:

2.625 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Surface Treatment:

Enamel

Style Designator:

Fixed

Fsc Application Data:

Power supply, guided missile remote control system, airborne

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0